

Primus blue

HL

HL053WS

HL053S

HL053Sblack

HL53 Shower channel system

HL53 New: Proven Strength – Purposefully Enhanced

The HL53 shower drain system has been technically optimized and adapted to meet modern construction requirements. Additional features, simplified installation, and the **Primus blue** hybrid odor barrier make HL53 a future-proof solution for barrier-free showers and modern buildings.

All Advantages at a Glance

- Precise positioning thanks to the integrated positioning frame **NEW**
- Fast and precise height adjustment due to installation feet with quick-clamping system **NEW**
- With **Primus blue** hybrid odor barrier Odor-tight even after drying out and backflow-safe **NEW**
- Suitable for modern tile coverings from 6 mm tile thickness **NEW**
- Additional design option in black for strong visual accents **NEW**
- Removable odor barrier for easy cleaning and free access to the pipe system. Ideal for shallow installations with low water pressure and increased risk of clogging
- Flat version HL53FPblue with only 65 mm installation height, ideal for renovation projects
- Flexible positioning: Suitable for installation both in the floor area and against the wall
- Compatible with previous HL53 shower channels

Technical Details:

Bauhöhen: 90 mm / 65 mm

Installation heights:
50 mm / 20 mm

Drainage capacity:
0,83 l/s bzw. 0,48 l/s

Suitable floor coverings:


HL053 S: 8–36 mm

HL053 M/P: 8–36 mm

Lengths:

HL053 S: 900, 1000 und 1200 mm (cuttable)

HL053 M/P: 800–1500 mm (cuttable)



Materials:



Odor barrier variants:

Water odor barrier
Water seal height: 50 mm
Drainage capacity: 0,83 l/s



Primus blue hybrid odor barrier
Drainage capacity: 0,48 l/s



Drain Bodies:

**HL53.0
HL53Prblue.0**
Drain body incl. odor barrier
Installation height: 90 mm



HL53FPblue.0
Drain body incl. odor barrier flat version
Installation height: 65 mm

