

PRODUCT - INFORMATION No. 1/ 2012

New at HL



HL50FU + HL50WU

Ultra flat shower channel with height „68 mm“



Product description

Additional to the existing shower channel series HL50 with height 110mm and 90mm HL is now able to supply an ultra-flat version with 68mm!

This enables the plumber, to install linear, barrier-free shower solutions at low floor constructions, like e.g. at reconstruction sites.

The drain body itself is equipped with a trap with 24mm water height and may be used only at showers, which are frequently used. For floor constructions, higher than 115mm we recommend as before the usage of shower channels with 5cm water height.

Concerning installation, possibilities of covers and the connection to the waterproofing there is no difference to the conventional shower channel.

The shower channel is available as “W”-version for installation close to the wall or as “F”-version for installation in the plain surface.

Product data:

- **Capacity:**
HL50FU + HL50WU length from 60cm -130cm 1 drain DN50 = 0,46l/s
Length from 140cm – 210cm with 2 drains DN50 = 0,82l/s
- **Rigid outlet DN50, may be converted by screwing by 180°.**

Advantages:

- **Height 68mm**
- **Same stainless steel shower channel, as standard version, therefore may be combined with all drain bodies.**
- **Removable trap for easy cleaning and access to the waste pipe.**
- **Installation and connection to the waterproofing as usual.**
- **Existing covers (Standard, Individual and Design) fit.**

Available: from now!

Price: Same as HL50-series